

DATA SHEET

CI801

System 800xA hardware selector



S800 I/O is a comprehensive, distributed and modular process I/O system that communicates with parent controllers and PLCs over industry-standard field buses. The CI801 Fieldbus Communication Interface (FCI) module is a configurable communication interface that performs operations such as signal processing, gathering of supervision information, OSP handling, Hot Configuration InRun, HART pass-trough and configuration of I/O modules. The FCI connects to the controller through of the PROFIBUS-DPV1 fieldbus.

Features and benefits

- PROFIBUS DP PROFIBUS-DPV1 fieldbus interface.
- Supervisory functions of I/O ModuleBus
- Isolated power supply to I/O modules
- OSP handling and configuration
- Input power fused
- Hot Configuration In Run
- HART pass-through

General info		
Protocol	PROFIBUS DP-V1	
Article number	3BSE022366R1	
Master or slave	Slave	
Line redundancy	No	
Module redundancy	No	
Hot Swap	No	
Used together with HI Controller	Yes	

Detailed data		
24 V consumption typ.	140 mA	

Environment and certification	
Temperature, Operating	0 to +55 °C
Temperature, Storage	-25 to +70 °C
Pollution degree	Degree 2, IEC 60664-1
Corrosion protection	ISA-S71.04: G3
Relative humidity	5 to 95 % no condensation
Protection class	IP20 according to EN60529, IEC 529
CE-marking	Yes
Electrical Safety	IEC 61131-2, UL 61010-1, UL 61010-2-201
Hazardous location	C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2
Marine certificates	ABS, BV, DNV-GL, LR
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)
WEEE compliance	DIRECTIVE/2012/19/EU

Dimensions	
Height	136 mm (5.35 in.) including latch
Width	85.8 mm (3.38 in.)
Depth	58.5 mm (2.30 in.)
Weight	0.3 kg (0.66 lbs.)



solutions.abb/800xA solutions.abb/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2021 ABB All rights reserved